

Harmagedhon POWER AMPLIFIER

A special output transformer guarantees the state-of-the-art performance of this final amplifier with more traditional - but not overly traditional - lines. Evoking the past with a new look, the Harmagedhon amp satisfies the mature, timeless taste of the most demanding audio mavens.



Technical Data

Type:	Solid State	Signal to noise:	120 DBV unweighed input shorted
Configuration:	Symmetrical dual mono in A class	Dumping factor:	> 1000
Technology:	Bipolar transistors	Rated power consumption:	400 W
Frequency response:	15 Hz - 50 MHz	Rated mains frequency:	50 - 60 Hz
Total harmonic distortion:	< 0,05% 20 Hz - 20 kHz	Weight:	35 kg (77 lbs)
Power output:	100 wrms per channel into 8 Ohms With no more than 0,05% THD	Dimensions:	H: 18 cm (7") W: 44,5 cm (17 1/2") D: 36,5 cm (14 1/3")
IM distortion:	< 0,05%	Special features:	Equipped with patented output transformer able to avoid the counter reaction factor, Cabinet in milled and polished aeronautical aluminium
Input impedance:	100 kOhms in parallel with 11 pf		
Sensitivity:	0,5 wrms in - for 50 wrms out (35 dB)		
Slew rate:	> 1000 V/us small and large signal		