

## Qoh' INTEGRATED AMPLIFIER

The essence of pure sound. Sublime in form. Completely remote-controlled and simple to operate, the Qoh integrated amplifier, with its 70 watts per channel, contains in a single component all the qualities and performance of the two racks that you have always dreamed of.



### Technical Data

Type:	Solid State	Inputs:	1 cd, 1 aux/video, 1 tuner, 1 tape, 1 phono via optional card mm or mc
Configuration:	Symmetrical dual mono in A/B class	Outputs:	1 tape, Loudspeaker set for biwiring
Frequency response:	DC - 50 Mhz (-3 dB)	Rated power consumption:	200 W
Total harmonic distortion:	< 0,05% 20 Hz - 20 kHz	Rated mains frequency:	50 - 60 Hz
Power output:	70 wrms per channel into 8 Ohms	Weigth:	25 kg (55 lbs)
	With no more than 0,05% THD	Dimensions:	H: 12 cm (4 3/4") W: 30 cm (12") D: 42 cm (16 1/2")
IM distortion:	< 0,05%	Special features:	Close tolerance controls, Handcrafted aeronautical aluminium chassis, High purity gold connectors, Designed by Enrico Lusuardi
Input impedance:	100 kOhms in parallel with 11 pf		
Sensitivity:	5 wrms in - for 70 wrms out (35 dB)		
Slew rate:	> 100 V/us small and large signal		
Signal to noise:	117 DBV unweighed input shorted		
Dumping factor:	> 1000		