

Ruah II PREAMPLIFIER

Japanese design inspires the simple lines of this horizontally-oriented preamp. Not merely a handsome front on a black box, the cabinet is made completely of solid-milled aeronautic-grade aluminium, for beauty from every side. Complete with a phono section for vinyl lovers, and aluminium or wood side handles, Ruah II is the ultimate for those who demand breathtaking performance.



Technical Data

Type:	Solid State	Slew rate:	> 1000 V/us small and large signal
Configuration:	Discrete components in A class	Signal to noise:	119 DBV unweighed input shorted
Structure:	Two chassis with separate regulated power supply	Inputs:	1 cd, 1 aux/video, 1 tuner, 1 tape, 1 adjustable phono
Frequency response:	DC - 50 Mhz (-3 dB)	Outputs:	2 mains, 1 tape
Total harmonic distortion:	< 0,05% 20 Hz - 20 kHz	Rated power consumption:	30 W
Voltage output:	15 vrms per channel into 50 Ohms With no more than 0,05% THD	Rated mains frequency:	50 - 60 Hz
IM distortion:	< 0,05%	Weight:	17 kg (37 lbs)
Input impedance:	100 kOhms in parallel with 11 pf	Dimensions:	H: 9 cm (3 1/2") W: 30 cm (12") D: 42 cm (16 1/2")
Sensitivity:	26 dB		