

Nefesh II POWER AMPLIFIER

Its 70 watts per channel allow it to handle all the loudspeaker on the market. Its natural dynamics and design make it unique in the world of amplifiers. It's Mel Audio and it's Italian!



Technical Data

Type:	Solid State	Signal to noise:	118 DBV unweighed input shorted
Configuration:	Symmetrical dual mono in A class	Dumping factor:	1000 wide band
Technology:	Bipolar transistors	Rated power consumption:	150 W
Frequency response:	DC - 50 Mhz (-3 dB)	Rated mains frequency:	50 - 60 Hz
Total harmonic distortion:	< 0,05% 20 Hz - 20 kHz	Weight:	20 kg (44 lbs)
Power output:	50 wrms per channel into 8 Ohms With no more than 0,05% THD	Dimensions:	H: 9 cm (3 1/2") W: 30 cm (12") D: 42 cm (16 1/2")
IM distortion:	< 0,05%	Special features:	Close tolerance controls, Handcrafted aeronautical aluminium chassis, High purity gold connectors, Designed by Enrico Lusuardi
Input impedance:	100 kOhms in parallel with 11 pf		
Sensitivity:	0,5 wrms in - for 50 wrms out (35 dB)		
Slew rate:	> 1000 V/us small and large signal		